

# HSAJET® Touch Controller

TIPC15

Windows driven controller with  
database connectivity prints  
for fully variable imprints

## HSAJET® Industrial Touch Printer Controller utilizes HP TIJ 2.5 technology

The Touch Industrial PC builds on the HSAJET® controller board (CB) solution driving reliable HP TIJ2.5 technology. The built-in controller board is PCI based and can control up to 2" of print height in any combination or orientation of 4 x 1/2" swaths.

### Industrial casing

The black anodised aluminium frame and steel case provide extra protection for harsh industrial environments.

### HSAJET Software

Specially designed software packages drive TIPC15 controllers:

- CODING & MARKING
- GRAPHICS & MAIL
- PHARMACEUTICAL

All HSA software solutions provide the features needed for their respective markets; examples include database connectivity, vision system control and unique serialization capability. All HSA software solutions provide an easy to use, intuitive design.

### Advanced software features

Stitching accuracy down to pixel level means printable objects can be located anywhere on the canvas without limitation.

All TIPC15 software packages offer flexible ink saving feature providing up to a 75% ink saving.

### Remote control

The comprehensive communication protocol allows you to control the unit remotely. Eight outputs allow for integration of the controller into the most complex systems.

Remote management is done through ethernet or serial connection.



### Powerful solution

The availability of different print head styles makes the system usable in a variety of applications printing horizontally or vertically/down.

The combination of hardware and software provides a powerful printing solution as a standalone solution or as part of an integrated application.

### Choose between standard or premium model

A standard model, as well as a premium model, is available. The standard model is perfect for running CB INKdraw or Mail INKdraw. The premium model is recommended for integration using a camera solution. For Pharma INKdraw the premium version is always required.

### Print at breakthrough speeds of up to 300 m/min in 300 x 150 dpi

- GRAPHICS
- COUNTERS
- SHIFT CODES
- DATE & TIME
- FIXED TEXT
- LINEAR & 2D BARCODES
- REAL-TIME PRINTING
- VARIABLE TEXT
- ANY WINDOWS TRUE TYPE FONT

# Technical Details

## HSAJET TOUCH INDUSTRIAL PRINTER CONTROLLER TIPC15-HP

### Technology

HP TIJ 2.5

### Printhead frequency

15 KHz

### Print height

50.8 mm / 2"

1, 2, 3 or 4 pen printheads

### Print head distance

0.5 - 2.0 mm

(nozzle to print surface)

### Voltage

100-240 VAC

### Memory

64MB (print buffer)

### Screen

15" colour Touch screen

### Design software

CB InkDraw (standard)

Mail InkDraw (optional)

Pharma InkDraw (optional)

### Software menu language

English (multiple languages)

### Print functionalities, eg.

User prompt

User defined print log

Barcode log

Error log

### Print features

Database printing (SQL - Txt - Access)

Left/Right, Upside-down

Other side, Inverted

Global Ink Reduction

### Layout features

Max. length 65000 px

(~277 cm in 600 DPI)

Object rotation in 90 deg interval

Link field content

Works with mm/inch/point/pixel

### Remote controlling

Create jobs

Edit jobs

Change field content per print

Change print preferences/parameters

### Interface

RS232 (serial)

100 Mb Ethernet (LAN)

USB

Camera connection (USB)

Control connection (SUB-D15)

Encoder Input 5-24V (SUB-D9)

Product Sensor 5-24V (SUB-D9)

### Signals

Low ink signal

Print signal

Print message signal

Stacker/bundle signal (option)

Resolution (DPI) (horizontal x vertical)	Max. speed (m/min)	
	m / min	feet / min
600 x 600	38	125
600 x 300 1 row	76	250
300 x 300	76	250
200 x 600	114	374
300 x 300 1 row	152	500
300 x 600	38	125
300 x 150	306	1000

Database change signal (option)

Database mark signal (option)

Batch count signal (option)

Check content/reject signal (option)

### Complies to

CE directives

### Housing

Black anodised aluminium frame


Stainless steel housing

### Weight

8.1 kg / 17.8 lbs

### Accessories

- Printheads (see other flyer)
- Distributor box
- USB Key / Stylus pen (included)
- Sensor and encoder
- Mountings (Inocon 53 mm)
- Prep. for Inocon FLV-25/ FLV-40/ FLS30-S1



TIPC15 PC min. configuration	Standard	Premium
Hard disk	160	160
RAM	1 Gb	2 Gb
Processor	1.5 Ghz	2 Ghz
Printing Software	CB INKdraw Mail INKdraw	CB INKdraw Mail INKdraw Pharma INKdraw
Operating System	Windows XP Pro	

DEALER:



HSA Systems Denmark

DK-2740 SKOVUNDE | +45 4494 0222 || DK-5260 ODENSE S | +45 6610 3401

HSA Systems France

F-93160 NOISY-LE-GRAND | +33 1 4815 5050

www.hsasystems.com | mail@hsasystems.com